## STEELBRO CONTAINER HANDLING SOLUTIONS

## SB450 RSH 2040

**Technical Specification** 


## 28/02/2024

Cranes		Chassis	
Crane Model	SB450	Chassis Model	Heavy Duty Rigid Chassis (40')
Max Lift Capacity	45 Tonne	Rubplate Height (RPH)	1350 mm (1225 mm optional)
Max Outreach	3910 mm (from centre-line)	Overall Height (OAH)	4229 mm (ISO 8'6" container)
Side of Lift	Right hand lift (Left hand lift optional)	Kingpin	Standard 2" (Bolted, dual position)
Stabilisers	Tilt & Extend (Foot size: 730x220)	Landing Legs	FUWA dual speed, wind up legs
Lifting Chains	16 mm Grade 120 RUD ICE	Landing Leg Handle	Right hand side
Chain Shorteners	Optional (not supplied)	Suspension	FUWA mechanical suspension
<b>Container Detection</b>	Container proximity sensor and lights	Axles	22.5 10/335 Drum brake
Work Lamps	Fitted to each stabiliser leg	Axle 1	Rigid
Hydraulics	Danfoss PVG32 proportional valve	Axle 2	Rigid
Crane Paint	Silver Grey (RAL 7001)	Axle 3	Rigid
Interface		Wheels	Steel 8.25x22.5 Dual
<b>Container Position</b>	Ramshift 20',2x20',40'	Tyres	11R 22.5
Control System	Analogue	Brake System	Air operated service brakes
Remote Control	Cable remote	Brake Coupling	Glad-Hands
Control Cabinet	Steel, lockable	Lighting	Multi-volt LED
Toolbox	Steel, lockable 915 mm (Grey)	Electrical Coupling	Socket 7-pin socket (ISO1185)
Container Joiners	To lift 2x20' ISO containers simultaneously	Mudguards	Plastic, Black
Power Supply		Mud Flaps	2x singles
Source	Kubota V2403 Diesel	Spare Wheel Carrier	Fitted
Spec	36.5 kW (49HP) at 2700rpm	Paint	Traffic Blue (RAL 5017)
Voltage	12V	Shipping configuration	Cut Chassis
Emissions	Tier4/Stage IIIA emissions		
Pump	Tandem Pump		
Mounting	Mounted between chassis rails		
Tank	Tank Oil/Diesel mounted to side of lift		



Sales DrawingSB450RS2040-G002-ITare Weight12500 kg ± 3% (Subject to final specification)





Page 2 of 2